

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation -

RAVENOL SCOOTER 4-Takt Fullsynth.

Art. 1151155

Description:

RAVENOL SCOOTER 4-Takt Fullsynth. is a fully synthetic high quality green coloured engine oil based on PAO for 4-stroke small engines. A specially designed additive package and a formulation with special ingredients for a high viscosity index ensure for a clean engine and clean inlet and exhaust systems and thus proper lubrication and wear protection.

RAVENOL SCOOTER 4-Takt Fullsynth. due to its special additives and the selection of base oils and its viscosity an energy-saving operation of engines. Due to its special active ingredients ensures **RAVENOL SCOOTER 4-Takt Fullsynth.** for a cleaner engine and clean inlet and exhaust systems.

RAVENOL SCOOTER 4-Takt Fullsynth. is the product for optimal life of the machine.

RAVENOL SCOOTER 4-Takt Fullsynth ensures an excellent cold start performance for optimum

Application Directions:

RAVENOL SCOOTER 4-Takt Fullsynth. is for use in 4 -Stroke engines.

Quality Classification:

RAVENOL SCOOTER 4-Takt Fullsynth. is tried and tested for aggregates specifying:

Specification: API SN

Recommendations: Yamaha, Honda, Aprilia, Suzuki, Kawasaki, Peugeot, Arctic Cat, Bombardier, Argo, Dinli, Polaris.

Technical Characteristics:

RAVENOL SCOOTER 4-Takt Fullsynth. offers:

- High wear protection
- Fuel efficiency by smooth running characteristics
- Excellent detergent and dispersant
- Prevents black sludge formation
- Long life due to high oxidation stability
- Excellent cold starting properties
- Very good viscosity-temperature behavior
- Low volatilization tendency

Technical Values:

Characteristics	unit	data	test according to
Colour		green	visual
Density	at 20°C	kg/m ³ 852	EN ISO 12185
Viscosity	at 40°C	mm ² /s 76	DIN 51 562
	at 100°C	mm ² /s 12,9	DIN 51 562
Viscosity index		171	DIN ISO 2909
Flashpoint (COC)	°C	232	DIN ISO 2592
Pour point	°C	- 45	DIN ISO 3016
TBN	mg KOH/g	10,5	DIN ISO 3771
Sulphated ash	%wt.	1,15	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

19.05.15