

- Certificate / ProductInformation -

**RAVENOL SCOOTER 4-Takt Teilsynth.**  
Art. 1152155

**Description:**

**RAVENOL SCOOTER 4-Takt Teilsynth.** is a semi-synthetic high quality green dyed motor oil for small 4-stroke engines. Special ingredients provide a clean motor and clean intake and exhaust systems. This provides impeccable lubrication and wear protection.

**RAVENOL SCOOTER 4-Takt Teilsynth.** enables an energy-saving operation of motors because of its additives and the selection of base oils and viscosity characteristics. Special ingredients in **RAVENOL SCOOTER 4-Takt Teilsynth.** provide for a clean motor and clean intake and exhaust systems. **RAVENOL SCOOTER 4-Takt Teilsynth.** is the product for an ideal service life of the engine.

**Application directions:**

**RAVENOL SCOOTER 4-Takt Teilsynth.** is for use in small 4-stroke engines.

**Quality Classification:**

**RAVENOL SCOOTER 4-Takt Teilsynth.** is tried and tested for aggregates specifying:

API SL

SAE 10W-40

Yamaha, Honda, Aprilia, Suzuki, Kawasaki, Peugeot, Arctic Cat, Bombardier, Argo, Dinli, Polaris.

**Characteristics:**

**RAVENOL SCOOTER 4-Takt Teilsynth.** offers:

- High wear protection
- Fuel saving due to smooth-running properties
- Excellent detergent and dispersant properties
- Prevention of black sludge formation
- Long service life due to outstanding oxidation stability
- Excellent cold start performance
- Very good viscosity-temperature characteristics
- Low tendency to evaporation

**Technical values:**

Characteristics	unit	data	test according to
<b>Colour</b>		green	visual
<b>Density</b>	at 20°C	868	EN ISO 12185
<b>Viscosity</b>	at 40°C	91.3	DIN 51 562
	at 100°C	14.0	DIN 51 562
<b>Viscosity index VI</b>		157	DIN ISO 2909
<b>Flash point COC</b>	°C	>200	DIN ISO 2592
<b>Pour point</b>	°C	- 35	DIN ISO 3016
<b>TBN</b>	mg KOH/g	7,1	DIN ISO 3771
<b>Sulphated ash</b>	%	1.5	DIN 51 575

All declared values are approximate and subject to standard commercial variations.