

- Certificate / Product information-

RAVENOL WATERCRAFT Teilsynth. 2-Takt

Art. 1152210

Description:

RAVENOL WATERCRAFT Teilsynth. 2-Takt is a semi-synthetic 2-stroke oil, dyed blue, on the basis of selected, high quality base oils and an ash-free additive package for optimum viscosity and corrosion protection.

Application directions:

RAVENOL WATERCRAFT Teilsynth. 2-Takt can be used in a mixture of up to 1:75 with regular petrol.

RAVENOL WATERCRAFT Teilsynth. 2-Takt is particularly suitable for the lubrication of air-cooled two-stroke petrol engines with high engine speeds and severe loads.

RAVENOL WATERCRAFT Teilsynth. 2-Takt is excellently suited for the lubrication of two-stroke watercrafts with water cooling systems.

RAVENOL WATERCRAFT Teilsynth. 2-Takt meets the requirements of the National Marine Manufacturers' Association NMMA TC-W3 (Yamaha CE 50S, Mercury).

Quality Classification:

RAVENOL WATERCRAFT Teilsynth. 2-Takt is approved, tried and tested for aggregates specifying:

API TC, ISO-L EGC, JASO FC

Approval: NMMA TC-W3®, RL-30010H

Technical characteristics:

RAVENOL WATERCRAFT Teilsynth. 2-Takt offers:

- Excellent lubrication of all engine parts
- A powerful cleaning performance, which keeps combustion chambers as well as intake and exhaust channels free of combustion residue and deposits to the greatest possible extent
- Clean spark plugs provide for an optimum performance of the engine
- Great wear and corrosion protection
- Low vehicle exhaust emission due to good combustion

Technical values:

Characteristics	unit	data	test according to
Colour		blue	
Density at 20°C	kg/m ³	877	EN ISO 12185
Viscosity at 40°C	mm ² /s	65,0	DIN 51 562
at 100°C	mm ² /s	9,5	DIN 51 562
Viscosity index		126	DIN ISO 2909
Flash point COC	°C	>100	DIN ISO 2592
Pour point	°C	-25	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.